



UNITÉ EXTÉRIEURE MAXI-MRV

22.5 KW - 28 KW - 33.5 KW
40 KW - 45 KW - 50 KW
56 KW - 61.5 KW



Model	ML- MRV-H250/ SR1MV	ML- MRV-H280/ 28k	ML- MRV-H330/ SR1MV	ML- MRV-H400/ SR1MV	ML- MRV-H450/ SR1MV	ML- MRV-H500/ SR1MV	ML- MRV-H560/ SR1MV	ML- MRV-H610/ SR1MV
Combinaison (HP)	8	10	12	14	16	18	20	22
Capacité refroidissement (KW)	25.2	28	33.5	40	45	50.4	56	61.5
Capacité Chauffage (KW)	25.2	28	33.5	40	45	50.4	56	61.5
Alimentation électrique (V,HZ,P)	380-415, 3, 50/60	380-415, 3, 50/60	380-415, 3, 50/60	380-415, 3, 50/60	380-415, 3, 50/60	380-415, 3, 50/60	380-415, 3, 50/60	380-415, 3, 50/60
Refroidissement absorbé (KW)	5.31	6.11	8.48	9.90	11.82	12.63	15.34	18.9
EER W/W	4.75	4.58	3.95	4.04	3.81	3.99	3.65	3.25
Chauffage absorbé (KW)	4.6	5.23	6.38	8.25	9.78	11.69	13.83	15.44
COP W/W	5.48	5.35	5.25	4.85	4.6	4.31	4.05	3.98
SEER	6.7	6.50	7.2	6.5	6.3	6	5.6	5.2
SCOP	4.2	4	4.2	4.3	4.2	4	3.6	3.5
Débit d'air (m³/h)	12000	12000	14000	16000	14000	16000	16000	16000
Niveau de pression sonore dB(A)	≤58	≤58	≤58	≤61	≤61	≤63	≤63	≤63
Type de compresseur	DC inverter	DC inverter	DC inverter	DC inverter	DC inverter	DC inverter	DC inverter	DC inverter
Nombre d'unité	1	1	1	1	1	2	2	2
Type de moto-ventilateur	DC Moteur	DC Moteur	DC Moteur	DC Moteur	DC Moteur	DC Moteur	DC Moteur	DC Moteur
Nombre d'unité	1	1	1	1	2	2	2	2
Nombre max des unité intérieur	13	16	20	23	26	30	33	36
Rapport de connexion %	50~200	50~200	50~200	50~200	50~200	50~200	50~200	50~200
Dimension (L.D.H) Net (mm)	990x765x1635	990x765x1635	990x765x1635	1340x765x1635	1340x765x1635	1340x765x1635	1340x765x1635	1340x765x1635
Dimension (L.D.H) Emballer (mm)	1030x825x1865	1030x825x1865	1030x825x1865	1395x815x1865	1395x815x1865	1395x815x1865	1395x815x1865	1395x815x1865
Poids net (Kg)	215	215	230	265	265	330	330	330
Poids brut (Kg)	225	225	240	280	280	345	345	345
Diamètre de tuyau,côté liquide (mm)	12.7	12.7	12.7	15.88	15.88	15.88	15.88	15.88
Diamètre de tuyau,côté gaz (mm)	22.2	22.2	22.2	28.6	28.6	28.6	28.6	28.6
Plage de fonctionnement,refroidissement °C	- 15 /52	- 15 /52	- 15 /52	- 15 /52	- 15 /52	- 15 /52	- 15 /52	- 15 /52
Plage de fonctionnement,chauffage °C	- 25 /24	- 25 /24	- 25 /24	- 25 /24	- 25 /24	- 25 /24	- 25 /24	- 25 /24