




UNITÉ INTÉRIEURE SYSTÈME MRV CONSOLE

4.50 KW - 5.60 KW - 7.10 KW
8 KW - 10 KW - 11.20 KW
12.50 KW - 14 KW



Model	ML-VCF-H045/ 4R1A	ML-VCF-H056/ 4R1A	ML-VCF-H071/ 4R1A	ML-VCF-H080/ 4R1A	ML-VCF-H100/ 4R1A	ML-VCF-H112/ 4R1A	ML-VCF-H125/ 4R1A	ML-VCF-H140/ 4R1A
Capacité refroidissement (KW)	4.5	5.60	7.10	8	10.00	11.20	12.50	14.00
Capacité Chauffage (KW)	5.00	6.00	8.00	10.00	12.00	12.80	13.30	15.00
Alimentation électrique (V,HZ,P)	220~240,50,1	220~240,50,1	220~240,50,1	220~240,50,1	220~240,50,1	220~240,50,1	220~240,50,1	220~240,50,1
Puissance nominale (W)	80	80	140	140	140	210	210	210
Débit d'air (m³/h)	950/760/665	950/760/665	1300/1040/910	1500/1200/1050	1500/1200/1050	1800/1440/1260	1800/1440/1260	1800/1440/1260
Niveau de pression sonore dB(A)	42/39/36	42/39/36	45/42/39	47/44/41	47/44/41	48/45/42	48/45/42	48/45/42
Dimension (L.D.H) Net (mm)	929×660×205	929×660×205	1280×660×205	1280×660×205	1280×660×205	1631×660×205	1631×660×205	1631×660×205
Dimension (L.D.H) Emballer (mm)	1010×720×290	1010×720×290	1360×720×290	1360×720×290	1360×720×290	1710×720×290	1710×720×290	1710×720×290
Poids Nette de l'unité intérieure (Kg)	26	26	35	35	35	45	45	45
Diamètre de tuyau,côté liquide (mm)	1/4"	1/4"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"
Diamètre de tuyau,côté gaz (mm)	1/2"	1/2"	5/8"	5/8"	5/8"	5/8"	5/8"	5/8"
Drainage (mm)	DN20(R3/4)	DN20(R3/4)	DN20(R3/4)	DN20(R3/4)	DN20(R3/4)	DN20(R3/4)	DN20(R3/4)	DN20(R3/4)
Cooling /Heating	✓	✓	✓	✓	✓	✓	✓	✓
Self Diagnosis	✓	✓	✓	✓	✓	✓	✓	✓
Golden Fin	✓	✓	✓	✓	✓	✓	✓	✓
Ventilateur Turbo	✓	✓	✓	✓	✓	✓	✓	✓
Afficheur LCD	✓	✓	✓	✓	✓	✓	✓	✓
Low voltage	✓	✓	✓	✓	✓	✓	✓	✓
Fresh Air	✓	✓	✓	✓	✓	✓	✓	✓